



PREPASTED NON-WOVEN DESIGN2WALL FR 230

satin 2515, 230 g/m²

Prepasted, flame retardant non-woven wallpaper for high traffic areas

Prepasted non-woven design2wall FR 230 satin is a high quality non-woven wallpaper with prepasted back, optimised for Solvent-, Latex- and UV inks. Due to the water activated paste on the back, the prints can be emerged with water and hung directly on the wall. The product is treated with flame retardant and C-s1, d0 certified. Thanks to the high scratch resistance, the surface of the wallpaper is resistant for long term use in areas frequently used. The prepasted coat allows long term adhesion on a variety of surfaces, while ensuring easy removability.

Advantages

- Time saving during application thanks to prepasted back
- Scratch resistant surface
- Good coverage of uneven surfaces
- Dimensionally stable, no wet or dry stretching
- Wide colour gamut
- Easy to remove
- Easy to handle
- Treated with flame retardant, C-s1, d0 certified



Technologies



Properties



- Dimensionally stable

General tips

To maintain the high quality of this non-woven, it should be stored and converted in a climate of 30-65% relative humidity and at temperatures of 10-30 °C (50-86°F).

Physical data

Name	Value	Norm
Weight [g/m ²]	230	ISO 536
Thickness (total) [µm]	350	ISO 534
Whiteness, CIE D65/2°	78	ISO 11476
Opacity [%]	85	ISO 2471
Gloss (60°)	5.4	ISO 2813

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technically modified printers and/ or inks. Product design changes to our products technical developments may be carried out without prior notice.