



# NON-WOVEN DESIGN2WALL FR 210

satin 2517, 210 g/m<sup>2</sup>

Flame retardant non-woven wallpaper for high traffic areas

Non-woven design2wall FR 210 satin is a high quality non-woven wallpaper for Solvent-, Latex- and UV-inks which stands out due to high colour brilliance and dimensional stability.

The product is treated with flame retardant and B-s1, d0 certified, which is especially important for commercial use. Due to the high scratch resistance, the surface of the wallpaper is resistant for long term use in areas frequently used.

## Advantages

- Scratch resistant surface
- Good coverage of uneven surfaces
- Dimensionally stable, no wet or dry stretching
- Wide colour gamut
- Easy to handle
- Treated with flame retardant, B-s1, d0 certified



## General tips

- To maintain the high quality of this non-woven, it should be stored and converted in a climate of 30-65% relative humidity and at temperatures of 10-30°C (50-86°F).
- After pasting the wall with a standard wallpaper paste, the wallpaper can be hung just like all other non-woven wallpapers. Thanks to its structure, it is easy to remove again and requires no additional protection.

## Physical data

Name	Value	Norm
Weight [g/m <sup>2</sup> ]	210	ISO 536
Thickness (total) [µm]	315	ISO 534
Whiteness, CIE D65/2°	78	ISO 11476
Opacity [%]	83	ISO 2471
Gloss (60°)	5.4	ISO 2813

## Technologies



## Properties



- Dimensionally stable