



BILLBOARDS / POSTERS

TRISOLV BILLBOARD PAPER PLUS 130 SATIN

satin 3687, 130 g/m²

Universal, satin matt, blueback poster paper for billboard applications

This multi-coated, weatherproof and water-resistant paper with a satin finish is suitable for printing with solvent, latex and UV-curing inks. Prints impress with high colour brilliance. TriSolv Poster Paper Plus 130 qualifies for outdoor billboard applications and displays good resistance to scratches and very good folding endurance. The opacity of the blueback ensures optimum coverage of substrates.

Technologies



Properties



Advantages

- Good colour brilliance
- Water-repellent surface
- Opaque blueback ensures good coverage of substrates
- Very good folding endurance



General tips

- Please note when printing with any of the 300 and 500 series HP Latex printer, to print roll to roll!
- The ink amounts must be adjusted to the paper. Please reduce the single colors cyan, magenta, yellow and black (ink restrictions) and shorten the maximum amount of ink (ink limit). This will help your costs on inks and improve your drying performance.
- Please follow the recommendations of the printer and ink manufacturer. The temperature for preheating and drying the media should be checked previously to make sure you will achieve desired results.
- Pasting application: After wetting the paper should be kept in a plastic box in order to wet the paper sufficiently. We recommend to keep the TriSolv Paper wet for at least eight hours. Longer periods of time don't have any negative impact on the paper. The user is responsible for appropriate microbiological precautions.
- In the event that the paper is exposed to severe climatic conditions, or if it needs to be used for a longer period of time, lamination is recommended. It is advisable to protect the edges and corners if the billboard hoarding is regularly cleaned.
- The TriSolv Papers blue back have passed the "Klebstest" of the Swiss billboard association, Allgemeine Plakatgesellschaft (APG). The application features are confirmed.
- To maintain the high quality of the paper, it should be stored and converted in a climate of 30 – 65 % relative humidity and at a temperature of 10 – 30 °C (50 – 86 °F).

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.

Physical data

Name	Value	Norm
Weight [g/m ²]	130	ISO 536
Thickness (paper) [µm]	150	ISO 534
Opacity [%]	> 98	ISO 2471
Gloss (85°)	51	ISO 2813
Chromaticity (D50/2°) M0	L*94.3 / a*1.3 / b*-4.4	ISO 13655, M0

The values stated above are only for orientation. Before using our print media please check its compatibility for your printer and the intended application. We cannot be held responsible for any mistakes resulting from technical changes in the printing process and with printing components. Product design changes to our products technical developments may be carried out without prior notice.