CAD-CUT® REFLECTIVE



INCREASE VISIBILITY IN LOW-LIGHT CONDI-TIONS, DIN 20471 CERTIFIED.

Reflective heat transfer material is thin, economical with a reflective finish. This material has a no-tack backing and is easy to cut and



silver reflective



AVAILABLE IN

50 cm x 25 m rolls

RECOMMENDED FABRICS

- 100% cotton
- 100% polyester*
- Polyester-cotton blends
- * Test before application!

IMPORTANT

Please remove the protection carrier before cutting.

CUTTING NOTES

You should always test cut prior to any production run. Remember cutter settings will need to be adjusted as the blade ages. For optimal cutting and weeding, maintain a line thickness of at least 2 mm (1/12") for lettering and logos.

APPLICATION INSTRUCTIONS

- Temperature: 150°C
- Time: 05 sec.
- Pressure: medium
- (#4-6 on Hotronix®)
- Peel: hot, Reseal for 05 sec.

MULTI-COLOUR DESIGNS

CAD-CUD® Reflective is not suitable for mulit-layer application.

ACCESSORIES RECOMMENDED

- **Grip Cover Sheet**
- Cover Sheet Non-Sticky
- EZ Weeder®

CARE INSTRUCTIONS

Machine wash up to 40° C using mild detergent. Do not use bleach. Dry at normal dryer settings on household machines. Do not dry-clean. Can be directly ironed.

STORAGE

Store in cool, dry area. Avoid direct heat, sunlight and humidity.

DETAILS







Easy weed



Ironable



Ironable only inside out



Washable



Sublimation



Stretchable



Flock









Multi-colour application



Peel hot



Application

